

SPECIFICATION

Part No.: NSF-A30W-RGB



NEWSTAR LED Lighting

Features

- No UV or IR light radiation.
- Easy Installation
- Long lifetime: 50000 hours
- Correlated Color Temperature: 2700-6500K
- AC100~240 V input.
- Working Voltage: DC30-36V
- LED type: 1 Module LED
- IP65 Protection grade
- 3 Years Warranty
- CE, RoHS Certified



Technical Specifications

Power	30W	CRI	>70
Lumens	2400lm	Color Temperature	RGB
Fixture efficiency	>0.90	Beam Angle	120°
Power Factor	>0.85	Frequency Range	50-60Hz
Light Source	Epistar LED	Dimension	225*185*126mm
Storage Temperature	-25°C ~ +65°C	Working Temperature	-30°C ~ +50°C
Body& Lampshade	Aluminum Alloy And PC	Weight	2.2KG

NEWSTAR LED Co., Ltd
LED Lighting Manufacturer In China
3-May-14 © 2014 NEWSTAR

Phone: +86-755-2940-5686
E-mail: info@newstarleds.com
<http://www.newstarleds.com>

SPECIFICATION

Application

- Shopping mall lighting.
- Exhibition hall lighting
- Parking lot lighting
- Gymnasium lighting
- park, sculpture and national green lighting project
- Tourist attractions lighting
- Green area lighting
- The building elevation of lighting
- Other light sources

